



# M150 WD

## Wet & Dry industrial vacuum

### FEATURES

The vacuum cleaners M 150 WD is powered by a by-pass motor, carbon brush type, providing a rapid cooling of the motor in case of overheating. The motors are installed inside a sturdy plastic case; special noise buffers reduce the noise within the safety standards of work. The suction inlet can be used with hoses ranging from 50 to 32 mm.

The filter is a polyester star filter, providing a filtration of 3 micron efficiency (cat. L),

The wet kit is made up by a floating device, protecting the motor against damage from liquids, foam and solid objects.

A 50 lt. container enables to dispose easily of the sucked up liquid, which can be discharged by a flexible discharge hose.

The frame is made of epoxidic painted steel and mounted on four wheels, two of them rotating and one with brake.

A complete wet & dry accessory kit (Ø38 mm.) is included

## Technical data sheet

MODEL - M150 WD		
<b>Tension</b>	Volt HZ	230 (110) 50/60
<b>Single phase motors</b>	N.	1
<b>Power</b>	Watt	1150
<b>Vacuum rate*</b>	mm.H2O	2.500
<b>Air flow**</b>	M3/h	180
<b>Dry Filter type</b>		Polyester
<b>Capacity</b>	Lt.	50
<b>Floating device</b>		Included
<b>Suction inlet</b>	∅	50
<b>Noise level</b>	dB(A)	72
<b>Dimensions</b>	cm.	52 x 40
<b>Height</b>	cm.	90
<b>Weight</b>	Kg.	20

\* Measured with fully closed suction inlet

\*\* Measured with fully open suction inlet

## Options

Cod	Description
X	Stainless steel collection tank