



M 450 WD - PROFESSIONAL WET & DRY



00

OPTICS



- ✓ Complete steel construction
- ✓ Three powerful by pass motors with independent cooling
- \checkmark Compact and mobile
- ✓ Accessory kit included

✓ Improved hygiene and operational conditions

¢ N

- ✓ Easy to handle
- ✓ Easy and safe to maintain
- \checkmark Easy to clean and to maintain

SUCTION UNIT		
Voltage	V - Hz	230 - 50 1 ~
Power	kW	3,45
Max waterlift	mmH2O	2.500
Max air flow	m³/h	540
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	76
FILTER UNIT		
Filter Type		Bag
Surface - Diameter	cm²-mm	8.000 - 500
Material - Efficiency	IEC 60335-2-69	Polyester - L
Media - Filtration		Polypropilene - 100µm
COLLECTION UNIT Discharge system		Discharge valve
\bigcirc	lt.	Discharge valve 120
Discharge system	lt.	
Discharge system Capacity	lt. cm	
Discharge system Capacity VOLUME		120

www.mastervacuums.com master@mastervacuums.com



SUCTION UNIT

The suction is provided by three by-pass motors, using carbon brushes, operated by independent switches and placed inside a sturdy steel casing, filled with soundproofing material.



A floating device stops the suction whenever the liquid in the container reaches the maximum level and prevents overflowing.

The polyester bag filter, placed inside the filtering chamber, guarantees a wide filtering surface and high resistance to dust passage and clogging.

COLLECTION UNIT

The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels , that make it suitable for mobile service even when used on rough surfaces. Thanks to a discharge valve, it is possible to easily and safely empty the container.

✓ STAINLESS STEEL COLLECTION TANK