

Applications: dry / wet for clean rooms

Footprint: very small size and mobile

Material: complete stainless steel structure

Filter: multiple stages of filtration, clean air exhaust

Speciality: Up to ISO4 conformity, compliant with GMP standards, easy to clean and autoclavable (up to 120 ° C, excluding the engine head)

Applicazione: polveri / liquidi per camere bianche

Ingombro: molto compatti e facilissimi da trasportare

Materiale: costruzione completa in acciaio inox

Filtro: Molteplici stadi di filtrazione, aria in uscita dall'aspiratore perfettamente pulita

Specialità: conforme fino a ISO4, conforme agli standard GMP, facile da pulire e disinfettare: autoclavabile (fino a 120°C, esclusa la testata motore)



Technical data / Dati tecnici

CC1000 D

Voltage / Alimentazione	V - Hz	230 - 50 1~
Power / Potenza	kW	1
Motor / Motore		Direct cooling
Max waterlift / Depressione max	mmH ₂ O	2900
Max air flow / Portata d'aria max	m ³ /h	175
Suction inlet / Ø bocchettone	mm	40
Solids capacity / Capacità solidi	lt.	5
Liquids capacity / Capacità liquidi	lt.	-
Noise level / Rumorosità (EN ISO 3744)	dB(A)	70
Dimensions / Dimensioni	cm	36x33x51h
Weight / Peso	kg	20
Dimensions / Dimensioni	cm	180x77x200h
Weight / Peso	kg	265
Components in contact with material / Componenti a contatto con il materiale		AISI316
Primary filter / Filtro primario		Bag / Sacco
Surface, diameter / Superficie, diametro	cm ² -mm	2.000 - 280
Media, class / Media, classe		Polyester - M PTFE
Cleaning system / Sistema di pulizia		-
Safe Bag / sacco monouso a perdere		1 Included/standard
Absolute filters / Filtri assoluti		
Upstream / In aspirazione		U15 Included/Standard
Downstream / Aria in soffiaggio		U15 Included/Standard
Upstream motor cooling air / Entrata aria raffr.		-
Downstream motor cooling air / Aria raffredd In soffiaggio		-

STANDARD VERSION/VERSIONI STANDARD

Code/Codice	Description/Descrizione
CC1000D-001	CLEANCONTROL 1000D

OPTIONALS UPON REQUEST / OPTIONAL SU RICHIESTA

Code/Codice	
U15/OUT - Downstream	Included /Standard
TA.0751.0000	
TA.0426.0000	D40 accessory kit / Kit accessori Dry D40
TA.0535.0000	Recommended D40 autoclavable accessory kit / Kit accessori autoclavabili Dry D40