

Applications: Fixed suction unit for direct extraction on production machinery
Footprint: Compact and horizontal construction
Material: Complete steel construction
Filter: Pocket filter with manual filter cleaning system
Speciality: Maintenance free motor, suitable for continuous duty applications 24/7
 Highly modular and suitable for integration on OEM machines and production lines

Applicazione: Unità di aspirazione fissa a bordo macchina
Ingombro: Compatta e sviluppata orizzontalmente
Materiale: Costruzione completa in acciaio
Filtro: Filtro a tasche con scuotifiltro manuale
Specialità: Modularità degli elementi per installazione su macchinari e linee di produzione



Technical data / Dati tecnici

		MBF 30
Voltage / Alimentazione	V - Hz	400 - 50 3~
Power / Potenza	kW	2,2
Electrical protection / Protezione elettrica	IP	65
Pressure relief valve / Valvola limitatrice		Included / incluso
Max waterlift / Depressione max	mmH ₂ O	2600
Continuous water lift / Depressione in continuo	mmH ₂ O	1900
Max air flow / Portata d'aria max	m ³ /h	318
Suction inlet / Ø bocchettone	mm	50
Capacity / Capacità	lt.	15
Disposable bag / Sacchetto monouso		1 included - 1 incluso
Noise level / Rumorosità (EN ISO 3744)	dB(A)	71
Dimensions / Dimensioni	cm	84x44x67h
Weight / Peso	kg	60
Primary filter / Filtro primario		Star / Tasche
Surface, diameter / Superficie, diametro	cm ² -mm	8.000 - 360
Media, class / Media, classe		Polyester - ANT M
Filter cleaning system / Sistema pulizia filtro		Manual / Manuale

STANDARD VERSION/VERSIONI STANDARD

Code/Codice	Description/Descrizione
MBF30MAN-001	MBF20 MAN

OPTIONALS UPON REQUEST / OPTIONAL SU RICHIESTA

Code/Codice
X - Stainless steel AISI 304 collection tank
XXX - Full Stainless Steel AISI 304 construction
MT - Earth grounding
SP - Singlephase vacuum unit (DBF20 only)