



M 450 AIR HD 19V - AIR POWERED



AVIATION



FOOD INDUSTRY



SHIPYARDS



CHEMICAL-PHARMACEUTICAL



- ✓ Largest surface filter in its category
- ✓ Integrated filter cleaning system
- ✓ Complete steel construction
- ✓ Extractable collection container with optional use of disposable bags
- ✓ Low noise level
- ✓ High filtration efficiency
- ✓ Powerful suction thanks to a multi-nozzle venturi unit



SUCTION UNIT

| | | |
|---------------------------|--------|-------|
| Air supply | lt/min | 1.530 |
| Air supply pressure | bar | 6 |
| Ø Air supply hose | mm | 20 |
| Max waterlift | mmH2O | 5.000 |
| Max air flow | m³/h | 465 |
| Suction inlet | mm | 80 |
| Noise level (EN ISO 3744) | dB(A) | 74 |



FILTER UNIT

| | | |
|-----------------------|----------------|-------------------|
| Filter Type | | Star |
| Surface - Diameter | cm²-mm | 30.000 - 500 |
| Material - Efficiency | IEC 60335-2-69 | Polyester - ANT M |
| Cleaning system | | Manual |



COLLECTION UNIT

| | | |
|------------------|-----|--------------------|
| Discharge system | | Roll-out container |
| Capacity | lt. | 100 |



VOLUME

| | | |
|------------|----|------------|
| Dimensions | cm | 62x62x160h |
| Weight | kg | 80 |



SUCTION UNIT

The suction is provided by a venturi compressed-air-driven suction unit, protected inside a strong steel chassis, which contains also sound absorbing material to minimize noise during service. The suction is developed by a venturi-type vented suction unit, protected inside a solid steel head, containing sound absorbing material that minimizes noise during service.

The head includes a pressure and a vacuum gauge, in order to detect the clogging of the filter



FILTER UNIT

The large surface star filter, located inside the filter chamber, is made of polyester and provides high resistance against clogging and passage of fine dust.

It is possible to clean the filter using an integrated mechanical system: an external lever shakes the filter vertically and enables to clean the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment.



COLLECTION UNIT

The vacuumed material is collected into a wheeled steel detachable container, which can be extracted for easy disposal and can be used with optional disposable bags, for safer and handier disposal.



OPTIONALS

- ✓ ABSOLUTE HEPA FILTER
- ✓ PTFE COATED FILTER CLASS M
- ✓ HEAT RESISTANT FILTER (UP TO 250° CELSIUS)
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER
- ✓ EARTH GROUNDING
- ✓ CYCLONE FOR FILTER PROTECTION
- ✓ SIEVE GRID AND DISCHARGE VALVE