







TS 400 PN - INDUSTRIAL THREE PHASE





CERAMICS AND POTTERY INDUSTRIES



BUILDING AND CONSTRUCTION













- ✓ Side channel blower motor , powerful and silent, totally maintenance free, suitable for continuous duty
- ✓ Tangential suction inlet with integrated separation cyclone
- ✓ Complete steel construction
- ✓ Extractable collection container with optional use of disposable bags
- ✓ Vacuum gauge to detect filter clogging
- ✓ High filtration efficiency
- ✓ Integrated automatic filter cleaning system
- ✓ Pressure relief valve for motor protection

SUCTION UNIT			
Voltage	V - Hz	400 - 50	
Power	kW	4	
Electrical protection	IP	55	
Max waterlift	mmH2O	3.200/2.600	
Max air flow	m³/h	420	
Suction inlet	mm	80	
Noise level (EN ISO 3744)	dB(A)	70	

Filter Type Cartridge Surface - Diameter cm²-mm 57.000	FILTER UNIT		
Surface - Diameter cm²-mm 57.000	Filter Type		Cartridge
	Surface - Diameter	cm²-mm	57.000
Material - Efficiency IEC 60335-2-69 Polyester - ANT M	Material - Efficiency	IEC 60335-2-69	Polyester - ANT M
Air load on filter m³/m²/h 74	Air load on filter	m³/m²/h	74
Cleaning system Automatic PN	Cleaning system		Automatic PN
Cartridge number 2	Cartridge number		2

Discharge system		Roll-out container	
Capacity	lt.	100	
VOLUME			
Dimensions	cm	66x118x187h	
Weight	kg	145	

COLLECTION UNIT





SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.



FILTER UNIT

A vacuum gauge enables to check constantly the state of the filter and detect possible clogging, warning the operator that the filter must be cleaned.

The suction inlet is tangential, with an internally welded cyclone that deflects the incoming material.

Cartridges are automatically cleaned by a pneumatic reverse pulse cleaning system. The system is automatic, timed and adjustable. A compressor can be installed (on demand) on the back frame to guarantee the required air supply.



COLLECTION UNIT

The vacuumed material is collected into a wheeled steel container, which can be extracted for easy disposal and can be used with optional disposable bags, for safer and handier disposal.

The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels , that make it suitable for mobile service even when used on rough surfaces.

OPTIONALS

- ✓ ABSOLUTE HEPA FILTER
- ✓ PTFE COATED FILTER CLASS M
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER
- ✓ EARTH GROUNDING
- ✓ LONGOPAC BAGGING SYSTEM
- ✓ PRESSURE RELIEF VALVE
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST