



TS HD 150 SE Z22 - INDUSTRIAL THREE PHASE



CEMENT



CERAMICS AND POTTERY INDUSTRIES



BUILDING AND CONSTRUCTION



METALWORKING



- ✓ Integrated filter cleaning system
- ✓ Tangential suction inlet with integrated separation cyclone
- ✓ Extractable collection container with optional use of disposable bags
- ✓ Pressure relief valve for motor protection
- ✓ Vacuum gauge to detect filter clogging
- ✓ Star-triangle switchboard
- ✓ Easy filter replacement
- ✓ Atex certified for Zone 22
- ✓ Suitable for high specific weight material



UNITÀ ASPIRANTE

Atex zones		ATEX Z22
Marking		II 3D Ex tD IIIB T135°C IP55 Dc
Voltage	V - Hz	400 - 50
Power	kW	15
Electrical protection	IP	65
Max water lift	mmH2O	6.000
Continuous water lift	mmH2O	5.400
Max air flow	m ³ /h	730
Suction inlet	mm	120
Noise level (EN ISO 3744)	dB(A)	78



UNITÀ FILTRANTE

Filter Type		Star
Surface - Diameter	cm ² -mm	70.000 - 560
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M
Cleaning system		SELF CLEAN



UNITÀ DI RACCOLTA

Capacity	lt.	160
----------	-----	-----



INGOMBRI

Dimensions	cm	180x77x200h
Weight	kg	220



UNITÀ ASPIRANTE

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It is designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.

A pressure relief valve protects the motor, providing additional air for cooling.



UNITÀ FILTRANTE

The suction inlet is tangential, with an internally welded cyclone that deflects the incoming material.

The filter is equipped with a semiautomatic cleaning system handled by the operator. A pneumatic cylinder shakes the star filter by a vertical shaking movement which causes the detachment of dusts and wastes from the filter. This way, the operator will be able to decide without any limits when to turn the vacuum cleaner off and to clean the filter.

The large surface star antistatic filter, located inside the filter chamber, is made of polyester and provides high resistance against clogging and passage of fine dust.



UNITÀ DI RACCOLTA

The vacuumed material is collected into a wheeled steel container, which can be extracted for easy disposal and can be used with optional disposable bags, for safer and handier disposal.



OPTIONALS

- ✓ FILTER FOR FINE DUST - CLASS M
- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ ANTISTATIC FILTER CLASS M
- ✓ ANTISTATIC FILTER CLASS L
- ✓ PTFE COATED FILTER CLASS M
- ✓ HEAT RESISTANT FILTER (UP TO 250° CELSIUS)
- ✓ REVERSE PULSE FILTER CLEANING
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER
- ✓ EARTH GROUNDING
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST